ROBUS®

QUALITY PRODUCTS BY LED GROUP

CAESAR 48W IP20 LED BATTEN, 4000K, 1.2M

RCA484012-01

PLEASE READ INSTRUCTION BEFORE COMMENCING INSTALLATION AND RETAIN FOR FUTURE REFERENCES.
! Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician

Note:
Product technical information and specification may change over time without prior notification. For the latest technical information please visit our web site www.ledgrouprobus.com.au

-20°C < Ta < +40°C, 220-240V ~ 50/60Hz, Class I, IP20
Luminaire is non-dimmable
Suitable for mounting on a normally flammable surface.

Installation

1. Ensure mains supply is switched off before commencing work.
2. Select suitable location for mounting luminaire
3. Expose the base by removing the screws. Remove diffuser/ LEDs from base. Unplug connector
4. Mark appropriate fixing hole positions on wall, check location of buried cables, pipes and other building services before drilling
5. Feed supply cables through cable entry hole and attach base to surface
6. Connect supply: Live – Brown, Neutral –Blue and Yellow/Green - Earth
7. Plug in connector, attach diffuser/ LEDs and tighten screws. Ensure that it is secure

Note: This luminaire has no user serviceable parts. If damaged, disconnect from mains and discontinue use.

ISO 9001:2008
EQA
QUALITY ASSURED COMPANY

C E

The Installation must be carried out by a qualified electrician

Issue 2 220116

1160mm
74mm
62mm

L   E   N